



## OFM-15W00

### 15.6" Full-HD PCAP Multi-Touch Fanless Open Frame Monitor

- > 15.6" Full-HD Open frame PCAP Touch Monitor
- > VGA, Display Port, HDMI input connectors
- > Audio phone jack in
- > USB type A for touch function
- > Slim & Strength Design
- > Fanless Operation from 0° ~ 45°C
- > 12V DC in (Option for wide voltage 9~36V DC in)
- > Various mounting kits compliance with OFT series
- > Option for Bi-Direction WIFI-6 Interactive Module for USB Signal and Image

#### Spec

<b>Expansion</b>	
<b>Expansion</b>	Option for Bi-Direction WIFI-6 Interactive Module for USB Signal and Image
<b>Panel</b>	
<b>LCD Size</b>	15.6", 16:9
<b>Display Type</b>	Full HD
<b>B/L Inverter/Converter</b>	LCD built in
<b>Resolution</b>	1920 x 1080
<b>Pixel pitch</b>	0.17925(H) x 0.17925(V)
<b>Luminance</b>	220 cd/m <sup>2</sup>
<b>Contrast ratio</b>	800
<b>Viewing angle</b>	85 (U), 85 (D), 85 (L), 85 (R)
<b>Response time</b>	30 ms
<b>Backlight</b>	LED
<b>Touch Type</b>	Projective Capacitive Multi-Touch supports up to 10 points
<b>Touch Light Transmission</b>	89 %
<b>Touch Controller</b>	EETI
<b>I/O</b>	
<b>HDMI</b>	1x HDMI input
<b>Display Port</b>	1x Display Port input
<b>VGA</b>	1x VGA input
<b>System Control</b>	
<b>LED Indicator</b>	Power Led
<b>Control Buttons</b>	OSD Function Key (Power/ Menu/ Up/ Down)
<b>Certifications</b>	
<b>Certification Information</b>	CE / FCC Class A
<b>Mechanical &amp; Environmental</b>	
<b>Operating Temperature</b>	0°C ~ 45°C
<b>Storage Temperature</b>	-20°C ~ 60°C
<b>Operating Humidity</b>	0% ~ 90% Relative Humidity, Non-condensing
<b>Dimension (W x L x H)</b>	387 x 235 x 46 mm
<b>Weight</b>	2.5Kgs
<b>Vibration Test</b>	1.5Grms, IEC 60068-2-64, Random, 5 ~ 500Hz, 0.5hr/axis
<b>Shock Test</b>	Operating: IEC 60068-2-27 testing procedures, 10G for operation mode
<b>Mounting Kit</b>	Option for Flush / Panel / Wall Mount with mounting kits
<b>VESA</b>	75 x 75 mm 100 x 100 mm
<b>Power Requirement</b>	+12V DC in
<b>System Fan</b>	Fanless
<b>Relative Humidity</b>	0~90% Relative Humidity, Non-condensing
<b>Fanless</b>	Yes
<b>Drop</b>	ISTA 2A, IEC-60068-2-32 Test:Ed
<b>Ordering Information</b>	
<b>Ordering Information</b>	<p>OFM-15W00-X0003-1R 15.6" 1920x1080 220nits LED Panel, Open Frame Monitor with P-Cap Touch HDMI in/DP in/VGA in/Audio Line in/USB(B) for touch/OSD key/speaker/12V input/Without Adapter</p> <p>ACC-OFT-15-FMT-01R Flush Mount Kits for OFT-15W series</p> <p>ACC-OFT-15-PMT-01R Panel Mount Kits for OFT-15W series</p> <p>ACC-OFT-15-WMT-01R Wall Mount Kits for OFT-15W series</p> <p>E1702031833R USA Power Cord</p> <p>E1702031000R EU Power Cord</p> <p>E1702031834R Japan Power Cord</p> <p>E1702031830R UK Power Cord</p> <p>E1702031831R Australia Power Cord</p>

